IN THE CLAIMS

Please amend the claims as follows:

Claim 1 (Canceled).

Claim 2 (Currently Amended): The method as claimed in claim [[1]] 17, wherein the composite laminate sheet or sheet blank is drawn by applying the punch directly to the side of the sheet or the sheet blank that is coated with the adhesive polymer film.

Claim 3 (Withdrawn - Currently Amended): The method as claimed in claim [[1]] 17, wherein the composite laminate sheet or sheet blank is drawn by applying the punch directly to the side of the sheet or the sheet blank that is not coated with the adhesive polymer film.

Claim 4 (Currently Amended): The method as claimed in claim [[1]] $\underline{17}$, wherein the thickness E_a of the steel sheet is less than 0.5 mm.

Claim 5 (Currently Amended): The method as claimed in claim [[1]] $\underline{17}$, wherein the total thickness E_p of the adhesive polymer film is greater than 0.2 mm.

Claim 6 (Currently Amended): The method as claimed in claim [[1]] 17, wherein the total thickness E of the composite laminate steel sheet is between 0.3 and 1.2 mm.

Claim 7 (Currently Amended): The method as claimed in claim [[1]] 17, wherein the polymer film is directly extruded onto the sheet.

Claim 8 (Withdrawn - Currently Amended): The method as claimed in claim [[1]] <u>17</u>, wherein the polymer film is formed before being applied to the steel sheet by hot lamination or by bonding using an adhesive.

Claim 9 (Currently Amended): The method as claimed in claim [[1]] <u>17</u>, wherein the polymer of the adhesive film is a thermoplastic polymer.

Claim 10 (Previously Presented): The method as claimed in claim 9, wherein the thermoplastic polymer is selected from polyolefins, polyesters, polyamides, and blends thereof.

Claim 11 (Withdrawn): The method as claimed in claim 9, wherein the polymer is functionalized by grafting with a carboxylic acid or a derivative thereof.

Claim 12 (Withdrawn - Currently Amended): The method as claimed in claim [[1]] 17, wherein, before the polymer film is applied to the steel sheet, it undergoes a corona discharge or flame treatment.

Claim 13 (Currently Amended): The method as claimed in claim [[1]] 17, wherein the steel sheet is subjected to a prior surface treatment to improve the adhesion of the polymer film to the sheet.

Claims 14-16 (Canceled).

Claim 17 (Currently Amended): A method for fabricating a composite laminate part,

comprising:

coating at least one side of a steel sheet, of which a thickness E_a is less than 0.65 mm

with one or more adhesive polymer films of which a total thickness E_p is equal to or greater

than 0.1 mm, to form a composite laminate steel sheet having a total thickness E, according

to which $E = E_a + E_p$,

optionally, cutting said sheet to form a blank, and then

forming by initially drawing the composite laminate sheet or sheet blank to obtain

said composite part, the drawing being carried out in a drawing tool comprising a punch, a

die, and a blank holder, by adjusting [[the]] a value of the material passage Pm between the

punch and the die, so that:

$$E - 0.80 \times E_p \le Pm \le E$$
.

Claim 18 (Previously Presented): The method as claimed in claim 17, wherein the

sheet is cut to form the sheet blank and the sheet blank has at least one dimension greater than

600 mm.

Claim 19 (Previously Presented): The method as claimed in claim 17, wherein the

composite laminate part is an external automotive body part.

Claim 20 (Canceled).

4